

Available Configurations:

RIS-FLANGE2-15ACV
1.5" inlet and outlet

RIS-FLANGE2-20ACV
2" inlet and outlet

ITEMS relating to this Product:

SERVICE KITS
SPRINGS



RIS-FLANGE2-20ACV

These valves are fitted in the suction line between the storage tank and dispenser, to prevent drainage and loss of suction. Easily maintained via screwed cap, and to install springs to gain head ratings for above ground tanks.

- Angled suction line check valves
- Available in 1.5" BSPT (f) RIS-FLANGE2-15ACV and 2" BSPT (f) RIS-FLANGE2-20ACV
- Can be fitted with springs to provide head ratings for above ground tanks
- Spring available: 3psi / 4psi / 5 psi / 7.5 psi / 11 psi (allow 1psi per 2 feet of head)
- Service kits available
- All fully leak tested before despatch

Materials:

BODY: Anodised aluminium
CAP: Anodised aluminium
POPPET: Stainless steel
POPPET SEAL: Viton
CAP SEAL: Viton O ring

Suitable for:

Petroleum Spirit (including
Ethanol Blends up to 90%)
Diesel
Bio Diesel / FAME Blends
In UK:
Not for use on Retail UST tanks

Document Ref:

DATA-RIS-FLANGE-ACV-121113

Weights:

15ACV = 1.36kg
20AC = 1.21kg