

Specifications:

Outlet Flange:

PCat fittings to suit all pipework systems.

Base Flange:

4 inch flanged base to suit RIS-FLANGE tanklids
flanged ports



RIS-FLANGE4-TEE-MK2
Flanged base to suit RIS-FLANGE
Tanklids, and flanged inlet face

RIS-FLANGE4-TEE-R2-MK2
Threaded base to suit traditional
tank lids, and Flanged inlet face.

Line Testing bung available for both models

Part of the RIS-FLANGE Range of Products, a comprehensive series of products to populate either Suction or Pressure system tank lids with high quality, efficient fittings that are easy to install, maintain and test. This system also allows simple dis-assembly and reconfiguration of layout on tanklids using only hand tools.

- High Quality machined bodies, ensure sealing and concentric base and top access.
- Lower installation costs - can be fitted to tanks in the factory or on site.
- Easy to fit to the tank lid, leak free fit to pipework.
- Suitable for use with Bio-Fuel blends up to 90%.
- Flange fitting on inlet (side) port minimises leak paths.
- Assembly includes gasket bolts and integral cage to secure drop tube and OPD.
- Compatible with all pipe-work brands.
- Flexible connectors available: make fitting/servicing easier, removing stress from pipework.

Materials:

Anodised Aluminium
Viton A (FKM)
Stainless Steel

Suitable for:

Petroleum Spirit (including
Ethanol Blends up to 90%)
Diesel
Bio Diesel / FAME Blends

Document Ref:

DATA-RIS-FLANGE4-TEE-MK2-150909

Related Documents

INS-RIS-FLANGE4-TEE