

### RIS-RISER-3F-MK2 (shown on right)

- Flanged top, flanged bottom
- RIS-RISER height (less cap) is 500mm flange face to flange face

### RIS-RISER-3F-BSP-MK2

- Flanged top, threaded bottom
- 3" BSPT threaded base, which allows fitment to traditional threaded port tank lids

### RIS-RISER-3T

- Flanged top, threaded adaptor
- RIS-RISER cap assembly to fit to your own riser, with 3" BSPP female fitting

### RIS-RISER-R4-3F

- Flanged top, flanged bottom, plus 4" BSPT retrofit male fitting
- RIS-RISER height (less cap) is 500mm flange face to flange face



- These units are designed to mount electric level cartridges of up to 80mm OD, by other manufacturers, directly to a RIS-FLANGE™ Tanklid System
- The flanged swivel cap assembly allows the cable to exit the RIS-RISER in a horizontal plane to any required orientation
- The ATEX approved and IP68 rated metal cable gland supplied comes with a standard 4.0 – 8.0mm bush

#### Materials:

Anodised Aluminium  
Zinc Passivated Mild Steel  
Stainless Steel

#### Suitable for:

Petroleum Spirit (including Ethanol Blends up to 90%)  
Diesel  
Bio Diesel / FAME Blends  
AvGas and Jetfuel

#### Document Ref:

DATA-RIS-RISER-151012

#### Installation instructions:

INS-RIS-RISER-151012