

RIS-FLANGE SYSTEM FITTINGS

2" Components for 2" Ports

Vents

- PLAIN VENT FITTING
RIS-FLANGE2-VENT
- OR
- TESTABLE VENT FITTING
RIS-FLANGE2-SO-VENT-MK2

Suction Systems

- SUCTION MODULE
RIS-FLANGE2-SUCTION-MK2
RIS-FLANGE2-SO-SUCTION-MK2-LT
- SYPHON VALVE - SUB-PUMP SYSTEM
RIS-FLANGE2-SYPHON-HI-MK2
RIS-FLANGE2-SYPHON-MED-MK2-LT
RIS-FLANGE2-SYPHON-LO-MK2
RIS-FLANGE2-SYPHON-LO-MK2-LT

Length of drop tube 3m as standard

Pressure Systems

- OUTLET KITS - SEE CENTRE PANEL FOR AVAILABLE OPTIONS

Dipping for Water

- DIPPING SYSTEM - FOR VR SYSTEMS
RIS-PRESSURE-DIP-FA whole assembly
RIS-PRESSURE-DIP-KEY spare key
- Length of drop tube 3m as standard

OPD float

- RIS-STOP FLOAT ASSEMBLY
(comes with main valve but is available as a spare)
RIS-STOP-FLOAT-KIT

Blanks

- BLANKING PLATE
RIS-FLANGE2-BLANK

Threaded Base Components for traditional tanklid ports (Retrofit to non RIS-FLANGE Lids)

PLAIN VENT / SUCTION FITTINGS
RIS-FLANGE2-VENT-R2 and RIS-FLANGE2-SUCTION-R2

TEST VENT FITTING
RIS-FLANGE2-SO-VENT-R2-MK2

TEST SUCTION FITTING
RIS-FLANGE2-SO-SUCTION-R2-MK2

Gauge riser
(includes cable entry)
RIS-RISER-3BSP and RIS-RISER-R4-3F

4" Threaded Components

- RIS-FLANGE4-TEE-R2-MK2
- TEST BUNG Available



Sub-Pump Accessories

Sub-pump by others

Pressure - Sub-Pump and ancillary fittings not supplied by Risbridger

Sub-Pump Outlet kits

- RIS-FLANGE2-SP-OLK-BLANK-FLFL
- RIS-FLANGE2-SP-DRAIN
- RIS-FLANGE2-SP-OLK-BLANK
- RIS-FLANGE2-SP-OLK-FLFL
- Sub-pump Twin Manifold

RIS-FLANGE4-RF-RISER

RIS-FLANGE4-SP-RISER

RIS-FLANGE2-SYPHON-HI

For pressure systems we offer three syphon valves of different heights to allow the syphoning of tanks to balance fuel levels

4" Components for 4" Ports

RIS-STOP OPD's

- 1000l/m overflow prevention valve
RIS-STOP-3GF Series - see Pt No MATRIX
Float Assembly is fitted in 2" port or in 4" port with adaptor plate - see 2" port fitting table
- Length of drop tube available in standard lengths (see Matrix)

Fill Tees

- Tee for drop tube mounted OPD's
RIS-FLANGE4-TEE, includes retaining cage
- Test bung also available to allow testing of whole fill line
- TESTING PLATE FOR TEE
RIS-FLANGE4-TEE-TEST

Gauging

- Gauge riser including cable entry
RIS-RISER-3F
- Also available for retrofitting to threaded port tanklids
- OR
- ADAPTOR PLATE - 3" Female
RIS-FLANGE4-R3

Blanks

- 4" Blanking plate for unused entries
RIS-FLANGE4-BLANK

RIS-STOP Installation tools

RIS-FLANGE-2-SUCTION-JIG

TESTING PLATE FOR TEE
RIS-FLANGE4-TEE-TEST

TESTING PLATE FOR TEE
RIS-FLANGE4-TEE-TEST

Tools and Tool kits

Risbridger produce special tools and test pieces to ensure that the products can be easily and safely fitted whilst protecting the high grade finish on the outer surfaces.

Please ask to see our Tools and Tool Kit Datasheets.

Optional 2" Flex Connectors for the above

OR

2" FLEXIBLE CONNECTOR - 130mm long
SFS-2-130-SFF-PCAT

2" FLEXIBLE CONNECTOR - 90mm long
SFS-2-90-SFF-PCAT

4" Adaptors

If no 2" ports are available you can use spare 4" ports with relevant base adaptor plate

4" Flange to 2" Flange
RIS-FLANGE4-2

4" Flange to 3" Female
RIS-FLANGE4-3F

4" Flange to 4" Female
RIS-FLANGE4-4F

4" Flange to 4" BSPT Male
RIS-FLANGE4-BSPT-M

Optional 4" Flex Connectors

4" FLEXIBLE CONNECTOR
250mm long
SFS-4-250-SFF-PCAT

4" FLEXIBLE CONNECTOR
320mm long
SFS-4-320-SFF-PCAT



Risbridger recommend the use of flexible connectors when fitting to RIS-STOP overflow prevention valves or RIS-FLANGE-TEES to allow for misaligned pipework, to prevent distortion or stress on the internal parts of the valves

Miscellaneous adaptors for 2" Ports

ADAPTOR PLATE - 2" Female
RIS-FLANGE4-R2

RIS-FLANGE2-2F

RIS-FLANGE4-R3

RIS-FLANGE2-35-M

Risbridger

Quality Engineering Solutions