

This 7 Series model fits a 1 US quart factory packed round container and comprises the following parts:

- 54 inch clear conductive PVC hose
- RH11524 swivel adaptor to fit A352 coupling (Agusta own supply)
- 1600 filter element (beta 200 = 4.6 micron)
- Stability base
- 'MIL-H-5606 MINERAL HYDRAULIC' and 'MIL-H-83282 HYDRAULIC FLUID' fluid identification plates
- Coupling not included



(Assembly shown with packing tube in place of oil can)

The special 1600 filter element (beta 200 = 4.6 micron, in accordance with ISO 16889) fitted to Risbridger equipment dispenses filtered fluids to a cleanliness level of DefStan 05/42 400F or ISO 4406 Class 17/15/12.

Improve reliability and service life of your aircraft engines and components. Using our quick disconnect couplings and high level filtration you will protect the fluid

- Cans of oil are fitted to the pump before opening, preventing contamination of contents
- Integral can opener and suction pipe
- Available for many fluid/aircraft/system types
- Integral 'No Filter - No Flow' safety valve
- Stability base prevents toggle straps collapsing the can and improves sealing

Applicable to the following aircraft models:
Agusta/Bell AB139 helicopter.

Materials:

Anodised aluminium
Acetal-homopolymer
Zinc plated steel
Stainless steel
Brass

Suitable for:

Mineral Hydraulic oils
(clear/black conductive PVC and polyurethane/nylon hoses)

Document Ref:

DATA-7197-170503